

# CE7000-AKZ

## SPECIALTY CUTTER FOR AFTERMARKET AUTOMOTIVE STYLING

The CE7000-130 AKZ cutter has been specifically designed for the aftermarket automotive industry.

Modified for the streamlined cutting of window tint film, paint protection film, paint masking pinstriping & graphics, a heavy duty precision servo motor delivers accurate cutting speeds of up to 39 inches per second with an unsurpassed 15 feet of tracking.

### FEATURES

- 450 Grams of Downforce
- 39 inch per-second Cutting Speed
- Precise Loupe for Easy Blade Adjustment
- Open Software Platform
- Ethernet Connectivity
- Thumb Drive Port



*High Performance Cutting for  
Window Tint & Paint Protection Film*

**WINDOW TINT • PROTECTION FILM • PAINT MASKING • VINYL LETTERING / GRAPHICS**

### ACCESSORIES

Accessories for the CE7000-130AKZ include an anti-static string kit for front and rear which reduces the static electricity common with PPF and tint films which can restrict media movement.

#### EACH UNIT INCLUDES:

- Standard Media Roll Rack
- Specialty Tint Blade
- Heavy Duty Stand
- Anti-Static Kit
- Dual Media Catch Basket  
*designed for dust-free  
continuous tracking and/or  
repetitive job operations.*



# CE7000-AKZ

## Specifications for Cutting Window Tint and Paint Protection Media

ITEM	CE7000-130AKZ
Maximum Cutting Area	50 in x 164 ft (762 mm x 50 m)
Compatible Media Widths	2 in to 53 in (50 mm to 919 mm)
Maximum Media Thickness	59.1 mil (1.48 mm)
Maximum Cut Speed	39 in/s (990 mm/s) at 45° diagonal
Programmable Cutting Force	Max. 4.41N (450gf) in 38 steps
Number of Push Rollers	4 Push Rollers
Programmable Resolution	GP-GL™: 0.1/.05/.025/.01mm; HP-GL®: 0.001 in (0.025mm); GP-GL™: 254, 508, 1016, 2540; HP-GL®: 1016
Command Modes	GP-GL™, HP-GL® (Selectable in command menu or auto detection)
Configuration	Grit roller with digital servo drive system
Interface	USB 2.0 High-speed / Serial RS-232C / Ethernet interface
Display Panel	3.7" Graphic type LCD with back-light (240dpi x 128dpi)
Compatible Media Types	Self-adhesive Vinyl Film, Amberlith™, Rubylith™, Sandblast Resist Rubber, Window Tint Film, Paint Protection Film, Automotive Paint Protection Film
Shipping Weight with Basket	121 lbs (54.9 kg)
Unit Dimensions with Basket	67" x 45.2" x 48"
Warranty	2 Years Standard Warranty for Parts & Labor 5 Year Extended Warranty option available within 90 days



For more information please contact: [cp.sales@graphtecamerica.com](mailto:cp.sales@graphtecamerica.com)