

Designed to Inspire Confidence --Right Out of the Box!

Now anyone can produce beautiful, professional engraving of text and scanned graphics right from their computer. Roland designed the EGX-20 to be remarkably easy to operate, even for beginners. The EGX-20 is large and powerful enough to handle a wide variety of engraving jobs, including awards, product serial numbers, office directories, personalized items and more, yet small enough to fit comfortably on your desktop. Thanks to its intuitive joystick and dial controls, operation is uncomplicated for both novices and experienced professionals. The EGX-20 includes everything you need to get started immediately, including a complete suite of engraving software.








Roland's Active Surface Tracking System (AST)

Among the most revolutionary of the EGX-20's features is its Automatic Surface Tracking System. AST automatically tracks the height of the material to ensure engraving at a consistent depth, even on bowed or non-uniform surfaces. Unlike systems that can take extensive trial and error to learn, AST makes setting the origin point and cutting depth effortless. Now you can produce consistently beautiful results with less learning time and less wasted materials.

How AST Works:

An automatic height sensor is attached to the lower end of the spindle unit. In addition to tracking the height of the material, AST controls the spindle and cutter height automatically. It also protects the surface from being scratched by cutting debris. A choice of three-different-diameter nose cones is included, allowing you to choose the most appropriate size, depending on the line thickness or curvature of the material.



 $^{\ast}\text{AST}$ may not be able to engrave some materials, depending upon their shapes and/or design.

Engrave a Wide Variety of Materials

With its 15,000-rpm spindle motor, the EGX-20 is powerful enough to engrave on a wide variety of popular materials, including acrylics, PVC, ABS, polycarbonate and wood. With the optional diamond scraper and burnishing attachment, you can also scribe light metals such as aluminum and brass for awards. Securing the material to the worktable is easy with the included adhesive sheet. Once you select the material to be engraved from the menu of the included software, the EGX-20 automatically determines optimum cutting speed and tool path, assuring smooth accurate results.

Powerful, Easy-to-Use Engraving Software Included

Included with the EGX-20 is a complete suite of software: Dr. Engrave for nameplate engraving, 3D Engrave for producing reliefs and Virtual MODELA for simulating finished work.

Dr.Engrave

- Converts Windows TrueType fonts into single-line fonts for scribing so you won't need to purchase new fonts.
- Imports database files (*.txt/csv) and automatically lays them out for fast engraving of nameplates in large quantities. A "V" cut function outlines borders for easy separation of individual plates.
- Accepts scanned images such as illustrations or company logos directly from your scanner and computer for engraving.
- . Quickly handles enlargement and reduction.

3D Engrave

- Adds thickness to bitmap images to create reliefs.
- Allows you to specify different engraving depths for various objects in a single design for added creativity.


Virtual MODELA

- Preview finished reliefs on screen prior to actual production.
- Lighting effects, material color and bitmap overlays can be added to represent the finished product.
- Accurately estimates engraving time.





3D Engrave



Desktop Engraver EGX-20 SPECIFICATIONS

Table size	220 (W) x 170 (D) mm (8-5/8 (W) x 6-11/16 (D) in.)
Table load weight	Maximum 1 kg (2.2 1b.)
Carriage cutting range	203.2 (X) x 152.4 (Y) x 31.8 (Z) mm (8 (X) x 6 (Y) x 1-1/4 (Z) in.)
Carriage operating speed	X and Y axes: 0.1 to 1 mm/s, 1 to 15 mm/s (0.0039 to 0.59 in./s)
	Z axis: 0.1 to 1 mm/s, 1 to 6 mm/s (0.0039 to 0.23 in./s)
Cutting-depth control	AST (Active Surface Tracking) system
Maximum cutting depth	3D Cutting mode: 0.05 to 7 mm (0.002 to 0.27 in.)
	Engraving mode: 0.05 to 1 mm (0.002 to 0.039 in.)
Cuttable materials	Composition: Resin (acrylic, modeling wax, ABS, polyacetal, polycarbonate, styrenefoam, etc.), wood, and plaster
	Maximum thickness: 30 mm (1-1/8 in.)
Resolution	0.01 mm/step (0.00039 in./step)
Spindle motor	12 W (DC motor)
Spindle rotating speed	4,000 to 15,000 rpm
Cutter diameter	3.175 mm (1/8 in.)
Interface*	Parallel (compliant with IEEE 1284)
Power supply	AC adapter
	Input: AC 100 to 240 V ±10%, 50/60 Hz Output: DC 19 V, 2.1 A
Power consumption	Maximum during operation: 0.6 A at 100 V, 0.27 A at 240 V
Operating noise level	Standby: Less than 45 dB (A)
	No-load operation: Less than 70 dB (A) (according to ISO 7779)
External dimensions	515.2 (W) x 368.3 (D) x 270.6 (H) mm (20-5/16 (W) x 14-1/2 (D) x 10-5/8 (H) in.)
Machine weight	10.9 kg (24 1b.)
Operating environment	Temperature: 5 to 40 °C (41 to 104 °F)
	Relative humidity: 35 to 80% (no condensation)
Included items and	AC adapter, power cord, cutter, cutter holder, depth regulator noses (large and small),
accessories	adhesive sheet for mounting material, test-use plate material, Roland Software Package CD-ROM, User's Manual

*USB Connectivity: You can connect the EGX-20 to your computer's USB port with the optional parallel to USB conversion cable (SX-UP2).

Available Options

. ,	r general engraving on acrylic and resin material
ZEC-A2013	Cemented carbide dia = 3.175, 114(L) x 0.127(W)
ZEC-A2025	Cemented carbide dia = 3.175, 114(L) x 0.254(W)
ZEC-A2051	Cemented carbide dia = 3.175, 114(L) x 0.508(W)
ZEC-A2076	Cemented carbide dia = 3.175, 114(L) x 0.762(W)
	graving large characters (not intended for deep engraving) on acrylic and resin mater
ZEC-A2150	Cemented carbide dia = 3.175, 114(L) x 1.52(W)
ZEC-A2190	Cemented carbide dia = 3.175, 114(L) x 1.91(W)
ZEC-A2230	Cemented carbide dia = 3.175, 114(L) x 2.29(W)
ZEC-A2320	Cemented carbide dia = 3.175, 114(L) x 3.175(W)
arter round cutter	s for engraving acrylic and resin material with high speed
ZEC-A2013-QR	Cemented carbide dia = 3.175, 114(L) x 0.13(W)
ZEC-A2025-QR	Cemented carbide dia = 3.175, 114(L) x 0.25(W)
220-A2023-QI	

Model No.	Description
Burnishing attachn	nent
ZB-20	Diamond scraper (ZDC-A2000) is required.
Adhesive sheet for	securing engraving material
AS-10	210 mm x 140 mm (8-1/4 in. x 5-1/2 in.), 10 sheets
Replacement spind	le motor
· ·	T () () D () DO O (()) ()
ZM-12	Tests conducted by Roland DG Corporation resulted in
ZM-12	motor life of approximately 1000 hours.
ZM-12 Replacement spino	motor life of approximately 1000 hours.
	motor life of approximately 1000 hours.
Replacement spinc	motor life of approximately 1000 hours.

Roland reserves the right to make changes in specifications, materials or accessories without notice. Your actual output may vary. For optimum output quality, periodic maintenance to critical components may be required. Please contact your Roland dealer for details. No guarantee or warranty is implied other than expressly stated. Roland shall not be liable for any incidental or consequential damages, whether foreseeable or not, caused by defects in such products. Windows, Windows NT are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries. All other trademarks are the property of their respective owners.



Roland DGA Corporation 15363 Barranca Parkway Irvine, CA. 92618-2201

800.542.2307 949.727.2100 949.727.2112 fax www.rolanddga.com