

Hi-Fi Express FP-740 Wide Format Inkjet Printer

Specifications

FP-740 Specifications		
Printing method		Piezo inkjet
Printing width		73.6 inches wide (1869mm)
Acceptable media width		28 to 74 inches wide (710 to 1879mm)
Ink cartridges	Type	Exclusive Sublimation Ink cartridge
	Capacity	8 Cartridges of 220ml each
	Colors	4 Colors (CMYK)
Printing resolution		Max 720 dpi
Distance accuracy (*1)		Error of less than +/- 0.3% of distance traveled, or 0.3 mm, whichever is greater
Media Take-Up System	Outer Roll Diameter	Max 7.06 Inches (180mm)
	Roll Weight	Ma 44lb. (20kg)
Interface		Ethernet (10Base-T /100Base-TX, automatic switching)
Power-saving feature		Auto sleep (compliant with the International ENERGY STAR® Office Equipment Program)
Power Supply	Power and Frequency	Printer Unit : AC 100~240V +/- 10% 50 / 60Hz Take-Up Unit : AC 100~240V +/- 10% 50 / 60 Hz
	Power Capacity	Printer Unit: 2A Take-up Unit: 0.1A
Power consumption	Printing mode	Printer Unit : Approx 118 W
	Standby mode	Approx. 55 W
Acoustic noise level	Printing mode	62dB(A) or less (According to ISO 7779)
	Standby mode	40dB(A) or less (According to ISO 7779)
Dimensions (with stands)		139.4 (W) x 29.9 (D) x 51.5 (H) inches (3539(W) x 758(D) x 1307(H) mm)
Weight (with stands)		589 lbs (267kg)
Recommended environment	Power on	Temperature 20 to 32 C (68 to 89.6F), Humidity 35 to 80 % (non-condensing)
	Power off	Temperature 5 to 40 C (41 to 104F), Humidity 20 to 80% (non-condensing)
Accessories Included		Power cord, AC Adapter, cable clamps, media reinforcement pipes, take-up core, tracking shafts, media flanges, stoppers, media clamps, drain bottle, replacement blade for separating knife, hexagonal wrenches, head-unit tool, software RIP, Roland-PrintServer CD-ROM, User's Manual, Setup Guide, Roland-PrintServer Network Settings Guide