

Specifications

| SP-540V Specifications | | | |
|--|---|--|--------------|
| Printing method / Cutting method | | Printing Piezo ink-jet method / Media moving method | |
| Printing width | | 7-5/16 to 53 in. | |
| Acceptable media widths | | 8-5/16 to 54 in. | |
| Acceptable tool | | CAMM-1 series cutter blade. | |
| Ink cartridges | Type | Exclusive ECO-SOL INK cartridges | |
| | Capacity | 220cc +/- 5cc | |
| | Colors | Black, Cyan, Magenta, Yellow | |
| Printing resolution | | Maximum 1440 dpi | |
| Setting range for the heater temperature | Pre-heater | 86° to 122° F (30° to 50 °C) | |
| | Dryer | 86° to 122° F (30° to 50 °C) | |
| Distance accuracy (When cutting) | | Error of less than +/- 0.4% of distance traveled, or +/- 0.3 mm, whichever is greater. When distance correction ([CALBRATION] -[CUTTING ADJ.]) has been preformed: error of less than +/- 0.2 % of distance preformed, or +/- 0.1mm, whichever is greater. | |
| Printing Speed | High Speed Banner | 360x720 dpi (4 pass) | 114 sq ft/hr |
| | High Speed Vinyl | 360x720 dpi (4 pass) | 66 sq ft/hr |
| | Standard | 720x720 dpi (8 pass) | 32 sq ft/hr |
| | High Quality | 1080x1080 dpi (18 pass) | 16 sq ft/hr |
| | High Quality | 720x1440 dpi (16 pass) | 19 sq ft/hr |
| Distance accuracy (When printing) | While the print heater and dryer are running. | Error of less than +/- 0.4 % of the distance traveled, or +/- 0.5mm, whichever is greater. | |
| | While the print heater or dryer are not running | Error of less than +/- 0.3 % of distance traveled, or +/- 0.3mm, whichever is greater. | |
| Cutting speed | | 11.8 in/sec | |
| Blade force | | 30 to 300gf | |
| Blade offset compensation | | 0.0 to 1.5mm | |
| Repetition accuracy (When cutting) | | 0.1mm or less (excluding stretching / contraction of media) | |
| Repetition between printing and cutting | | +/- 0.5mm max. at 75°F (25°C) (excluding possible shift caused by expansion/contraction of the media and/or by reloading the media) | |
| Interface | | Ethernet (10 BASE-T / 100 BASE-TX, automatic switching) | |
| Power-saving function | | Automatic sleep feature (Compliant with the International ENERGY STAR Office Equipment Program) | |
| Power supply | Voltage and frequency | AC 100 to 120 V +/- 10% 50/60 Hz or AC 220 to 240 V +/- 10% 50/61 Hz | |
| | Required power capacity | 8.8 A (100 to 120 V) or 4.7 A (220 to 241V) | |
| Power consumption | Printing mode | Approx. 1080W (100 to 120 V) or 1230 W (220 to 240V) | |
| | Sleep mode | Approx. 30W | |
| Acoustic noise level | Printing mode | Approx. 64dB (A) or less (according to ISO 7779) | |
| | Standby mode | Approx. 40dB (A) or less (according to ISO 7779) | |
| Dimensions (with stand) | | 94.9" [W] x 31.5" [D] x 50.9" [H] | |
| Weight (with stand) | | 328 lb. | |
| Packed dimensions | | 100.1" [W] x 32.7" [D] x 47.4" [H] | |
| Packed weight | | 440 lb. | |
| Environment | Power on | Temperature: 59° to 90°F (15° to 32°C) 68°F (20°C) or more recommended Humidity: 35 to 80% (no condensation) | |
| | Power off | Temperature: 41° to 104°F (5° to 40°C) Humidity: 20 to 80% (no condensation) | |
| Included items | | Exclusive stand, cleaning liquid cartridges, power cord, small media clamps, large media clamps, blade, blade holder, replacement blade for separating knife, cleaning kit and manuals | |