

CUTTER SOLUTIONS



VINYL CUTTERS
BRING GRAPHICS TO LIFE

from Roland, our full line of performance vinyl cutters accelerate your ability to create professional signs, displays, vehicle graphics, decorated apparel and window tinting. Each comes with all the hardware and software you need to get started immediately

- right out of the box.

With plug-and-play ease, technological sophistication,



CUTTER SOLUTIONS

GX PRO SERIES CUTTERS

GX-300 GX-400 GX-500

Astounding value. Outstanding performance.

Speed. Power. Precision. The Roland GX Pro lets you shift your graphics business into high gear. Powered by digital servomotors, these professional grade vinyl cutters achieve maximum accuracy and cutting speeds up to 33-inches per second with up to 350 grams of pressure. Vehicle graphics, window tint, signage, labels, stencils and even pinstriping come out crisp and clean.

These professional-grade cutters also include an optical registration system, making it fast and easy to contour

cut full color pre-printed graphics. The ability to mate an existing printer with the GX Pro gives you a powerful and cost-effective print/cut solution. This feature lets you blow the doors off the transfer graphics for T-shirts, full-color

Roland CutStudio™



Roland CutStudio™

software included

2-year warranty with registration



SV-8 | SV-12 | SV-15

The ultimate portable vinyl cutters.

Easy to use. Affordable. Versatile. Roland STIKA design cutters let small offices, schools and hobbyists produce a wide range of custom graphics. The STIKA makes it easy to create everything from POP displays and iron-on graphics for T-shirts to vehicle graphics.

The STIKA also makes a cost-effective print/cut solution. Just print registration marks on your graphics with your desktop printer. Load the printed graphics into the cutter. And set the position of the registration marks using the STIKA driver. Making professional-looking graphics with the STIKA is a snap.



SV-12 \$735 US **SV-15** \$1,045 US

DESKTOP SIGNMAKER

CAMM-1 SERVO GX-24

The perfect companion for print-and-cut jobs.

Look under the hood of the Roland CAMM-1 SERVO GX-24 vinyl cutter and you'll find an advanced digital servomotor that ensures accuracy when cutting anything from reflective vinyl and paint mask, to twill, heat transfer and sandblast material. Perfect for print-and-cut jobs with its optical registration system that accurately aligns preprinted material for contour cutting, and built-in curve-smoothing function that ensures precision cutting even at top speeds of up to 20-inches per second. Simply connect your computer to the USB interface, pan through functions on the easy-to-read LCD screen, and use the included CutStudio $^{\mathsf{TM}}$ drawing software to create incredible graphics.

CAMM-1 SERVO GX-24 \$2,095 US

nal Catch Basket







REV UP YOUR PROJECTS WITH PROFESSIONAL-QUALITY SOFTWARE TOOLS.

Roland cutters include Roland CutStudio™ software. CutStudio™ lets designers quickly



and easily create graphics, position text on curves, enlarge, reduce, re-position, rotate and mirror images. Designs can be imported in BMP, JPG, STX, AI, and EPS file formats.

CutStudio™ includes a Windows XP/Vista printer driver, a plug-in for Adobe® Illustrator® 9/10/CS/CS2/CS3/CS4, a plug-in for CoreIDRAW® 10/11/12/X3/ X4, and a plug-in for Adobe Illustrator 9/10/CS/CS2/CS3/CS4 in the Macintosh OS 9/X environment. Roland cutters also work with all popular sign making software for maximum flexibility.

Roland VersaWorks is powerful RIP software



developed by Roland engineers for the company's inkjet technology and built upon the genuine Adobe® PostScript® CPSI™ RIP engine. For those customers who already own a Roland inkjet device, your VersaWorks RIP Software features an efficient graphical user interface that allows users to maximize their Roland inkjet through offline cutting without sacrificing print production.

OWNING A ROLAND



Your Roland ownership
experience is our #1 priority
and begins the moment you
complete your purchase. Our
Roland Care Passport is the
industry's most extensive

bundled service and support contract, giving you access to Roland warranties, on-site installation and training, e-mail and telephone technical support, user forums, newsletters and more. Roland also offers a variety of training courses through Roland University to help you build your business with important new skills.

PRODUCT SPECIFICATIONS

Interface

Weight

Warranty

Power supply

Dimensions (external)

Standard accessories

GX-300	GX-400		GX-500		GX-24	
29 x 984-1/8" (737 x 24,998 mm)	39 x 984-1/8" (1000 x 24,998 mm)		47 x 984-1/8" (1195 x 24,998 mm)		2 to 27.5" (50 to 700 mm)	
2 to 36" (50 to 915 mm)	3-1/2 to 46" (90 to 1178 mm)		3-1/2 to 54" (90 to 1372 mr	n)	Width: 22.9" (584 mm) Length: 984" (25 mm)	
33 in/sec (850 mm/sec) [in all directions]				4 to 20 in/sec (10 to 500 mm/sec)		
20 to 350 gf				30 to 250 gf		
Serial (RS-232C compatible), USB (Rev. 1.1)				USB interface (compliant with Universal Serial Bus Specifications Revision 1.1		
AC 100 V to 240 V +/- 10% 50/60 Hz 1.2 A	AC 100 V to 240 V =/- 10% 50/60 Hz 1.1A				Dedicated AC adapter; Input: AC 100 to 240 V +/- 10% 50/60 Hz 1.7 A Output: DC 24 V, 2.8 A	
With stand 45-1/16 (W) x 28-5/8 (D) x 43-13/16" (H) 1144 (W) x 727 (D) x 1113 mm (H)	With stand 55-3/8 (W) x 28-5/8 (D) x 43-13/16* (H) 1407 (W) x 727 (D) x 1113 mm (H)		With stand 63-1/16 (W) x 28-5/8 (D) x 43-13/16* (H) 1602 (W) x 727 (D) x 1113 mm (H)		33.5 (W) X 12.2 (D) X 9.25" (H) 851(W) X 310 (D) X 235 mm (H)	
With stand 97 lb. (44 kg)	With stand 112.4 lb. (51 kg)		With stand 121.2 lb. (55 kg)		35 lb. (16 kg)	
Power cord, blade, blade holder, alignment tool, cable clamp, replacement blade for separating knife, Roland Software Package CD-ROM, startup guide, user manual				AC adapter, power cord, blade, blade holder, separating knife, roller base, tweezers, test-use material, application tape, USB cable, "Roland Software Package CD-ROM," user's manual		
3 years on the GX Pro (with registration)				2 years on GX-24 (with registration)		
V-15		SV-12 S		SV-8	SV-8	
13-3/8 (X) x 39-5/16" (Y) [340 (X) x 1000 mm (Y)]		9-13/16 (X) x 39-5/16" (Y) [250 (X) x 1000 mm (Y)] 6-		6-1/4 (X) x 3	6-1/4 (X) x 39-5/16" (Y) [160 (X) x 1000 mm (Y)]	
Width: 14-1/8 to 15" (360 to 381 mm) Width: 11 to 12" (280 to 305 mm) Length: 43-1/4" (1100 mm) or less	11 to 12" (280 to 305 mm)				Width: 7-13/16 to 8-7/16" (200 to 215 mm) Length: 43-1/4" (1100 mm) or less	
7/16 to 3-7/8 in/sec (12 to 100 mm/sec)	3-7/8 in/sec (12 to 100 mm/sec)		7/16 to 1-9/16 in/sec (12 to 40 mm/sec)		7/16 to 1-9/16 in/sec (12 to 40 mm/sec)	
	29 x 984-1/8" (737 x 24,998 mm) 2 to 36" (50 to 915 mm) 33 in/sec (850 mm/sec) [in all directions] 20 to 350 gf Serial (RS-232C compatible), USB (Rev. 1.1 AC 100 V to 240 V +/- 10% 50/60 Hz 1.2 A With stand 45-1/16 (W) x 28-5/8 (D) x 43-13/16" (H) 1144 (W) x 727 (D) x 1113 mm (H) With stand 97 lb. (44 kg) Power cord, blade, blade holder, alignment Roland Software Package CD-ROM, startup 3 years on the GX Pro (with registration) SV-15 13-3/8 (X) x 39-5/16" (Y) [340 (X) x 1000 m) Width: 14-1/8 to 15" (360 to 381 mm) Width: 11 to 12" (280 to 305 mm) Length: 43-1/4" (1100 mm) or less	29 x 984-1/8" (737 x 24,998 mm) 39 x 984-1/8 2 to 36" (50 to 915 mm) 3-1/2 to 46" 33 in/sec (850 mm/sec) [in all directions] 20 to 350 gf Serial (RS-232C compatible), USB (Rev. 1.1) AC 100 V to 240 V +/- 10% AC 100 V to 50/60 Hz 1.2 A With stand 45-1/16 (W) x 28-5/8 (D) x 43-13/16" (H) 1144 (W) x 727 (D) x 1113 mm (H) With stand 97 lb. (44 kg) With stand 1 Power cord, blade, blade holder, alignment tool, cable clar Roland Software Package CD-ROM, startup guide, user maximum and supplies and	29 x 984-1/8" (737 x 24,998 mm) 2 to 36" (50 to 915 mm) 33 in/sec (850 mm/sec) [in all directions] 20 to 350 gf Serial (RS-232C compatible), USB (Rev. 1.1) AC 100 V to 240 V +/- 10% 50/60 Hz 1.2 A With stand 45-1/16 (W) x 28-5/8 (D) x 43-13/16" (H) 1144 (W) x 727 (D) x 1113 mm (H) With stand 97 lb. (44 kg) Power cord, blade, blade holder, alignment tool, cable clamp, replacement blade for sepa Roland Software Package CD-ROM, startup guide, user manual 3 years on the GX Pro (with registration) SV-15 13-3/8 (X) x 39-5/16" (Y) [340 (X) x 1000 mm (Y)] Width: 14-1/8 to 15" (360 to 381 mm) Width: 11 to 12" (280 to 305 mm) Length: 43-1/4" (1100 mm) or less	29 x 984-1/8" (737 x 24,998 mm) 39 x 984-1/8" (1000 x 24,998 mm) 47 x 984-1/8" (1195 x 24,998 mm) 3-1/2 to 54" (90 to 1372 mm) 33 in/sec (850 mm/sec) [in all directions] 20 to 350 gf Serial (RS-232C compatible), USB (Rev. 1.1) AC 100 V to 240 V +/- 10% 50/60 Hz 1.1A With stand 45-1/16 (W) x 28-5/8 (D) x 43-13/16" (H) 1407 (W) x 727 (D) x 1113 mm (H) With stand 97 lb. (44 kg) With stand 112.4 lb. (51 kg) With stand 121.2 lb. (55 kg) Power cord, blade, blade holder, alignment tool, cable clamp, replacement blade for separating knife, Roland Software Package CD-ROM, startup guide, user manual SV-15 13-3/8 (X) x 39-5/16" (Y) [340 (X) x 1000 mm (Y)] Width: 14-1/8 to 15" (360 to 381 mm) Width: 11 to 12" (280 to 305 mm) Length: 43-1/4" (1100 mm) or less	29 x 984-1/8" (737 x 24,998 mm) 2 to 36" (50 to 915 mm) 3 -1/2 to 46" (90 to 1178 mm) 3 in/sec (850 mm/sec) [in all directions] 20 to 350 gf Serial (RS-232C compatible), USB (Rev. 1.1) AC 100 V to 240 V +/- 10% 50/60 Hz 1.2 A With stand 45-1/16 (W) x 28-5/8 (D) x 43-13/16" (H) 1144 (W) x 727 (D) x 1113 mm (H) With stand 97 lb. (44 kg) Power cord, blade, blade holder, alignment tool, cable clamp, replacement blade for separating knife, Roland Software Package CD-ROM, startup guide, user manual SV-15 13-3/8 (X) x 39-5/16" (Y) [340 (X) x 1000 mm (Y)] Width: 14-1/8 to 15" (360 to 381 mm) Width: 14-1/8 to 15" (360 to 381 mm) Width: 14-1/8 to 15" (360 to 381 mm) Width: 14-1/4" (1100 mm) or less 47 x 984-1/8" (1195 x 24,998 mm) 3-1/2 to 46" (90 to 1178 mm) 47 x 984-1/8" (1195 x 24,998 mm) 3-1/2 to 54" (90 to 1372 mm) 47 x 984-1/8" (1195 x 24,998 mm) 3-1/2 to 54" (90 to 1372 mm) 47 x 984-1/8" (1195 x 24,998 mm) 3-1/2 to 54" (90 to 1372 mm) 47 x 984-1/8" (1195 x 24,998 mm) 3-1/2 to 54" (90 to 1372 mm) 47 x 984-1/8" (1195 x 24,998 mm) 3-1/2 to 54" (90 to 1372 mm) 47 x 984-1/8" (1195 x 24,998 mm) 3-1/2 to 54" (90 to 1372 mm) 47 x 984-1/8" (1195 x 24,998 mm) 3-1/2 to 54" (90 to 1372 mm) 47 x 984-1/8" (1195 x 24,998 mm) 3-1/2 to 54" (90 to 1372 mm) 47 x 984-1/8" (1195 x 24,998 mm) 47 x 984-1/8" (1195 x 24,998 mm) 3-1/2 to 54" (90 to 1372 mm) 47 x 984-1/8" (1100 x 24,998 mm) 47 x 984-1/8" (19 to 54" (90 to 1372 mm) 47 x 984-1/8" (10 to 1372 mm) 48 x 1.14 to 12" (280 to 305 mm) 48 x 1.14 to 12" (280 to 305 mm) 48 x 1.14 t	



13-3/8 (W) x 8-1/8 (D) x 4-1/2" (H) 340 (W) x 205 (D) x 115 mm (H)

4.9 lb. (2.2 kg)

17-3/8 (W) x 8-1/8 (D) x 4-1/2" (H)

440 (W) x 205 (D) x 115 mm (H)

6 lb. (2.7 kg)

AC adapter, power cord, USB cable, replaceable blade protector, blade, blade holder, pin, material for test cuts, application tape for test cuts,

Dedicated AC adapter input: AC 100 V +/- 10%, 50/60 Hz 1.7 A Output: DC 19 V 2.1 A

Roland Software Package CD-ROM, SV-15/12/8 user's manual

20-5/8 (W) x 8-1/8 (D) x 4-1/2" (H)

522 (W) x 205 (D) x 115 mm (H)

7.3 lb. (3.3 kg)